



ENAPART



93 S Railroad Avenue Unit C
Bergenfield NJ 07621 USA
www.enapart.com
sales@enapart.com



Via del Canneto 35,
Borgosatollo, Brescia - Italia
www.enapart.it
vendite@enapart.it



Barbaros Mah. Ihlamur Bul. Aĝaoĝlu
My Newwork No:3/15 Ataşehir / İstanbul
www.enapart.net
satis@enapart.net



PRIVADA 10 B SUR #3908 COL.
ANZUREZ, C.P. 72530, PUEBLA, PUE
www.enapart.com.mx
sales@enapart.com.mx



Friedrich-Ebert-Anlage 36, 60325
Frankfurt am Main, Germany
www.enapart.de
anfrage@enapart.de



4 boulevard Carnot, 95400
villiers-le-bel, Paris, France
www.enapart.fr
sales@enapart.fr



65049, ОДЕСА, ВУЛИЦЯ ІВАНА
ФРАНКА, БУДИНОК 55, ПОВЕРХ 3
www.enapart.com.ua
sales@enapart.com.ua



MUNICIPIUL BUCUREȘTI, SECTOR 3,
B-DUL BASARABIA, NR.250, CORP P+5
www.enapart.ro
sales@enapart.ro



〒584-0023 大阪府富田林市若松町
東2丁目2番16号
www.enapart.co.jp
sales@enapart.co.jp



PLAZA NUESTRA SEÑORA DE LAS
NIEVES 12 ,LOCAL ,50012,ZARAGOZA
www.enapart.es
ventas@enapart.es



Складова база „Онгъл“, Склад А2, п.к.
4006, гр. Пловдив, България
www.enapart.bg
sales@enapart.bg



3 Austin Mews, High Street, Hemel
Hempstead, HP1 3AF , United Kingdom
www.enapart.co.uk
sales@enapart.co.uk

| Size | GSA dimensions | | | | | | F _o | F _A ' | Transmissible torques or axial forces | | Weight WT |
|----------|----------------|----------------|--------|----------------|-------|-------|----------------|------------------|---------------------------------------|-----------------|--------------|
| | d | C ₁ | D | C ₂ | L | I | | | T | F _{ax} | |
| | Inch | | | | | | | | psi | lb-in | |
| GSA-250 | 0.2500 | | 0.3750 | | 0.126 | 0.094 | 580 | 450 | 14 | 112 | 0.76 |
| GSA-312 | 0.3125 | +0 | 0.4375 | -0 | 0.143 | 0.112 | 686 | 670 | 26 | 166 | 1.04 |
| GSA-375 | 0.3750 | -0.0005 | 0.5000 | +0.0005 | 0.160 | 0.128 | 673 | 920 | 43 | 229 | 1.35 |
| GSA-437 | 0.4375 | | 0.5937 | | 0.176 | 0.143 | 796 | 1196 | 65 | 297 | 2.20 |
| GSA-500 | 0.5000 | | 0.6562 | | 0.193 | 0.158 | 944 | 1512 | 94 | 376 | 2.69 |
| GSA-562 | 0.5625 | | 0.7500 | -0 | 0.210 | 0.174 | 1259 | 1872 | 132 | 469 | 3.97 |
| GSA-625 | 0.6250 | | 0.8125 | +0.001 | 0.226 | 0.187 | 1231 | 2237 | 175 | 560 | 4.69 |
| GSA-687 | 0.6875 | | 0.8750 | | 0.243 | 0.203 | 1414 | 2670 | 230 | 669 | 5.47 |
| GSA-750 | 0.7500 | +0 | 0.9375 | | 0.260 | 0.219 | 1413 | 3145 | 295 | 787 | 6.33 |
| GSA-812 | 0.8125 | -0.001 | 1.0312 | | 0.276 | 0.234 | 1617 | 3637 | 370 | 911 | 8.56 |
| GSA-875 | 0.8750 | | 1.0937 | -0 | 0.293 | 0.250 | 1611 | 4188 | 458 | 1047 | 10.14 |
| GSA-937 | 0.9375 | | 1.1875 | +0.0015 | 0.310 | 0.267 | 2087 | 4790 | 561 | 1197 | 12.36 |
| GSA-1000 | 1.0000 | | 1.2500 | | 0.326 | 0.284 | 2090 | 5437 | 680 | 1360 | 14.05 |
| GSA-1125 | 1.1250 | +0 | 1.4060 | | 0.359 | 0.312 | 2220 | 6620 | 840 | 1493 | 19.55 |
| GSA-1250 | 1.2500 | -0.0015 | 1.5310 | | 0.393 | 0.344 | 2240 | 8105 | 1140 | 1824 | 23.54 |
| GSA-1375 | 1.3750 | | 1.6870 | | 0.426 | 0.376 | 2745 | 9750 | 1510 | 2196 | 31.22 |
| GSA-1500 | 1.5000 | | 1.8120 | -0 | 0.459 | 0.407 | 3030 | 11510 | 1940 | 2587 | 36.38 |
| GSA-1625 | 1.6250 | +0 | 1.9680 | +0.002 | 0.492 | 0.437 | 3295 | 13390 | 2450 | 3015 | 46.43 |
| GSA-1750 | 1.7500 | -0.002 | 2.1250 | | 0.526 | 0.469 | 3585 | 15475 | 3045 | 3480 | 58.53 |
| GSA-1875 | 1.8750 | | 2.2500 | | 0.559 | 0.500 | 3595 | 17675 | 3730 | 3979 | 66.22 |
| GSA-2000 | 2.0000 | | 2.4060 | | 0.592 | 0.528 | 5365 | 19910 | 4480 | 4480 | 81.09 |
| GSA-2250 | 2.2500 | | 2.6560 | | 0.592 | 0.528 | 4795 | 22400 | 5670 | 5040 | 90.30 |
| GSA-2437 | 2.4375 | | 2.8430 | | 0.592 | 0.528 | 4430 | 24260 | 6655 | 5461 | 97.07 |
| GSA-2500 | 2.5000 | +0 | 2.9060 | -0 | 0.592 | 0.528 | 4330 | 24885 | 7000 | 5600 | 99.50 |
| GSA-2687 | 2.6875 | -0.003 | 3.0930 | +0.003 | 0.592 | 0.528 | 4035 | 26750 | 8090 | 6020 | 106.26 |
| GSA-2750 | 2.7500 | | 3.1560 | | 0.592 | 0.528 | 3950 | 27370 | 8470 | 6160 | 108.70 |
| GSA-3000 | 3.0000 | | 3.4060 | | 0.592 | 0.528 | 3890 | 29860 | 10080 | 6720 | 117.90 |

* Stainless steel available upon request.

* Delivery on request; other sizes stocked. Contact Ringfeder Corporation for additional sizes and information.

■ Selection Guide

1. Determine the shaft diameter to be used and the maximum torque (T) to be transmitted.

$$T = \frac{63,000 \text{ (lb-in)} \times \text{HP}}{\text{RPM}}$$

2. Select a locking element from the specification table for the shaft diameter. Verify that the transmissible torque (T) for the element meets the torque requirement.

Note: Required peak torque should never exceed specified transmissible torque (T). Higher torque capacities can be obtained by increasing the locking force.

3. Determine the required locking force (F_A'). A pre-load (F_O) is required to bridge the clearance for the specified fits. The total required locking force is F_A' = F_O + F_A'. The locking force is normally obtained by using one or more screws and a clamp plate.

4. Refer to screw tables on page 40 to determine the number, size and grade of screws needed for the required locking force and individual screw clamp load.

$$\text{Clamp load/screw} = \frac{\text{required locking force (F}_{A}'\text{) or F}_{A}'\text{'}}{\text{number of screws (z)}}$$

Explanations to tables

d, D, L, l = Basic dimensions, Locking Elements not tightened

C_1 = shaft tolerances

C_b = hub bore tolerances

C_2 = bore tolerances

A_t = effective bearing surface $A_t = \pi \cdot d \cdot l$

X = travel distance for 1,2,3 or 4 Locking Elements. This value includes a safety allowance to ensure that the thrust flange will not contact the face of the hub or shaft. Any reduction of this value could cause a block and the transmission values of the connection would not be achieved.

T = transmissible torque

F_{ax} = axial forces

T and F_{ax} refer to a pressure between the Locking Element and shaft of 14500 psi .

When solid Locking Elements the required total clamping force F_A is obtained by:

$$F_A = F_{A'} + F_O$$

$F_{A'}$ = Screw number x Fv, see screw table page 40

F_O = approximate clamping force required to bridge the clearances where the tolerances given in the table are fully exploited during manufacture, not applicable if slit Locking Elements are used.

d_1 = clamp plate bore

D_1 = spacer sleeve OD

T_{max} = transmissible torque by one Locking Element at a shaft contact pressure of = 47850 psi



Weitere technische Hinweise befinden sich im jeweiligen Katalog.

Alle technischen Daten und Hinweise sind unverbindlich. Rechtsansprüche können daraus nicht abgeleitet werden. Der Anwender ist grundsätzlich verpflichtet zu prüfen, ob die dargestellten Produkte seinen Anforderungen genügen. Änderungen, die dem technischen Fortschritt dienen, behalten wir uns jederzeit vor. Mit Erscheinen dieses Kataloges werden alle älteren Prospekte und Fragebögen zu den gezeigten Produkten ungültig.

Check out the respective catalogue for further technical details

All technical details and information is non-binding and cannot be used as a basis for legal claims. The user is obligated to determine whether the represented products meet his requirements. We reserve the right at all times to carry out modifications in the interests of technical progress. Upon the issue of this catalogue all previous brochures and questionnaires on the products displayed are no longer valid.

RINGFEDER POWER TRANSMISSION GMBH

Werner-Heisenberg-Straße 18, D-64823 Groß-Umstadt, Germany · Phone: +49 (0) 6078 9385-0 · Fax: +49 (0) 6078 9385-100
E-mail: sales.international@ringfeder.com · E-mail: sales.international@gerwah.com

RINGFEDER POWER TRANSMISSION USA CORPORATION

165 Carver Avenue, P.O. Box 691 Westwood, NJ 07675, USA · Toll Free: +1 888 746-4333 · Phone: +1 201 666 3320
Fax: +1 201 664 6053 · E-mail: sales.usa@ringfeder.com · E-mail: sales.usa@gerwah.com

RINGFEDER POWER TRANSMISSION INDIA PRIVATE LIMITED

Plot No. 4, Door No. 220, Mount - Poonamallee Road, Kattupakkam, Chennai – 600 056, India
Phone: +91 (0) 44-2679-1411 · Fax: +91 (0) 44-2679-1422 · E-mail: sales.india@ringfeder.com · E-mail: sales.india@gerwah.com

KUNSHAN RINGFEDER POWER TRANSMISSION COMPANY LIMITED

German Industry Park, No. 508 Hengguanjiang Road, Zhangpu Town 215321, Kunshan City, P.R. China
Phone: +86 (0) 512-5745-3960 · Fax: +86 (0) 512-5745-3961 · E-mail sales.china@ringfeder.com